



NOTES

- Safety zone provided at works locations
- All signing to be in accordance with The Traffic Signs Manual, Chapter 8 tables A1.2
- Size & spacing of cones & rates of taper in accordance with Traffic Signs Manual, Chapter 8, table A1.3
- Existing signs in conflict with this scheme to be covered/ dropped
- Works access/exit locations to be agreed on site
- Signs fixed to existing street furniture where possible with Highway Authority approval
- Pedestrian ramps to be used where no drop down kerbs are located
- A minimum footpath width of 1.2m must be maintained for pedestrian access
- A minimum carriageway width of 3.25m must be maintained in order to operate single file traffic
- A minimum carriageway width of 6.5m must be maintained in order to operate two-way traffic

MAP KEY

- Footway closed
- Pedestrian barrier
- Pedestrian route
- Carriageway closed
- Traffic cones
- No parking cones
- Traffic barrier
- Works area
- Aspect of sign vision
- Manual traffic control
- Temporary traffic signal
- Dimensional
- Direction of traffic
- Works Vehicle (3.5T)
- Works Lorry (7.5T)

Please note this drawing has been produced for the specified project and client as listed below and is not intended for the purpose of any other activity/ persons

Project EIGHT20	Drawn G.C.O	Approved
Contract No 1820	Checked	Date 17/10/2019
Title TRAFFIC MANAGEMENT PHASE 1 NORWOOD ROAD	Scale NTS	Drawing No 1820/ 02 REV G

**TRAFFIC
CONSULTANCY
LIMITED**